



DENIS OIL®
Additives & Lubricants

TECHNOLOGY FROM USA

Lubricant engine oil for 4T motorcycle

ENDU MAXSPEED SJ
SAE: 20W50

API SJ - JASO MA2

DENSYNTECH (technology to increase optimal engine power)

- It is specially formulated from selected Semi-synthetic base oil and synthetic additives from the US
- The product utilizes Densyntech technology to increase optimal engine power
- Products meet API SJ and JASO MA2 standards

Product features:

- Optimal prevention of wear, rust, and clutch slide
- Protect engine very well, save fuel and use oil for longer
- Ensuring engine performance in extreme operating conditions

Use

- Suitable for motorcycle engines of brands: Honda, Kawasaki, Suzuki, Yamaha, SYM ...

Safe to use:

- Please read MSDS before use
- Keep out of reach of children
- Limit contact with skin and and limit inhaling oil mist
- Wash hands with soap and clean water immediately after use
- Keep away from heat, sparks and open flames, even from empty bottles
- Avoid spilling oil into drains and rivers
- Confidential information is a trade secret

Storage and transport:

- Transport by vehicle with roof and vertical storage of the product
- Store in a cool, dry place

Manufactured according to standards: 50-2018 / Denis oil

Specifications:

Characteristic	Test method	Test result
Kinematic viscosity at 100 °C	ASTM D 445	Min 16,5
Viscosity index (VI)	ASTM D 2270	Min 105
Base number by potentiometric titration (mg KOH/g)	ASTM D 2896	Min 4
Flash point (COC), °C	ASTM D 92	Min 220
Foaming characteristic at 93,5 °C , MI	ASTM D 892	Max 50/0
Water content (by vol/ mass), %	ASTM D 95	Max 0.05

- The above are typical figures with generally accepted manufacturing tolerances and not specifications
- Product of: DENIS OIL CHEMICAL VIETNAM CO., LTD
- Importing and packing at: ICD JSC TAN CANG - LONG BINH, SAI GON NEWPORT CORPORATION (SNP)
- NO.10, PHAN DANG LUU, LONG BINH WARD, BIEN HOA CITY, DONG NAI PROVINCE.